

EcoFoot2+ Install Guide Appendix - UL2703 Qualification

Ecolibrium Solar® EcoFoot2+ Flat-Roof Ballasted Racking System

Ecolibrium Solar's EcoFoot2+ product has been tested in accordance with the ANSI/UL2703-2015 Standard for Mounting Systems, Mounting Devices, Clamping/Retention Devices, and Ground Lugs for Use with Flat-Plate Photovoltaic Modules and Panels. This testing standard includes subjecting samples of the racking to temperature and humidity cycling to simulate component aging, electrical bonding tests on all system components, system grounding tests, tests to verify that use of the system does not increase the risk of fire, and module-specific mechanical load testing.

EcoFoot2+ racking maintains a Class A fire rating when installed in landscape or portrait orientation according to the installation instructions, on a low slope roof Class A roof with Type 1 and Type 2 modules. For roofs with lower fire ratings, the existing rating is maintained when EcoFoot2+ is used.

EcoFoot2+ module clamps and wind deflectors are certified as recognized components under UL2703 for system electric bonding when installed with the below listed modules. Rows within an array, having a fuse rating of up to 25 amps, may be grounded via a single properly sized ground lug acting as a Grounding Electrode Conductor (GEC). The Ecofoot2+ install guide contains instructions for bonding and grounding modules if deviation from standard installation is required. Per UL2703, the EcoFoot2+ system creates a continuous bonded structure with all the below listed modules when installed per instructions in the install guide.

Mechanical load testing has been conducted in 2 ways. Firstly, load testing has been completed on system components that have been subject to temperature and humidity cycle tests. This verifies the long-term stability of all materials and components used. Secondly, the modules listed below have been mechanically load tested to the UL2703 standard. The module manufacturer and all approved module series are listed with the resulting load ratings in the table below.

UL2703 System Label: The label shown below is stamped into to the Wind Deflector (identified as component E in the installation guide).



The Date Code ABCYZZ shown above will appear on production parts, letters defined as follows:

- ABC shall be an acronym for identifying the source factory
- Y shall be the Quarter of the year (i.e. 1, 2, 3, 4) of manufacture
- ZZ shall be the last 2 digits of the year of manufacture

The below listed modules are listed for mechanical loading, grounding and bonding according to UL2703. The table continues next page. *Note: "XXX" represents module wattage*

Manufacturer	Module Series	Max. Downforce w/Mid-span Supports	Max. Downforce w/o Mid-span Supports	Max. Uplift			
Boviet Solar	BVM6612 P-XXX	50 psf	30 psf	11.8 psf			
	BVM6612 P-XXX (BB)						
	BVM6612-M-XXX						
	BVM6612 M-XXX (BB)						
	BVM6610P-XXX						
	BVM6610M-XXX						
	BVM6610M (BB)-XXX						
Canadian Solar	BVM6610P (BB)-XXX	50 psf	25 psf	13.3 psf			
	CS6P-XXXP				N/A	30 psf	30 psf
	CS6P-XXXM					30 psf	30 psf
	CS6X-XXXP				50 psf	38 psf	15 psf
	CS6U-XXXP				50 psf	25 psf	13.3 psf
	CS6U-XXXM						
ET Solar	CS6U-XXXP (1500V)	40 psf	20 psf	15.0 psf			
	CS6U-XXXM (1500V)						
	ET-M672XXXWW						
	ET-M672XXXWB						
	ET-P672XXXWW						
	ET-P672XXXWB						
Hanwha Q Cells	ET-M672XXXBB	55 psf	20 psf	15.1 psf			
	ET-P672XXXBB						
	Q.PRO BFR-G4 XXX						
	Q.PLUS BFR-G4.1 XXX						
	Q.PRO BFR-G4.1 XXX						
	Q.PRO BFR-G4.3 XXX						
	Q.PEAK-G4.1 XXX						
	Q.PEAK-G4.1/MAX XXX						
	Q.PEAK BLK G4.1 XXX						
	Q.PRO G4 XXX						
	Q.PLUS G4 XXX						
	Q.PEAK-G4.1/TAA XXX						
	Q.PEAK BLK G4.1/TAA XXX						
	Q.PLUS BFR G4.1/TAA XXX						
Q.PLUS BFR G4.1/MAX XXX							
B.LINE PLUS BFR G4.1 XXX							
B.LINE PRO BFR G4.1 XXX							
Q.PRO EC-G4.4 XXX							



Manufacturer	Module Series	Max. Downforce w/Mid-span Supports	Max. Downforce w/o Mid-span Supports	Max. Uplift
Hanwha Q Cells (con't.)	Q.PLUS L-G4.2 XXX	33 psf	30 psf	10.2 psf
	Q.PEAK L-G4.2 XXX			
	Q.PLUS L-G4.1 XXX			
	Q.PLUS L-G4 XXX			
	Q.PRO L-G4 XXX			
	Q.PRO L-G4.1 XXX			
	Q.PRO L-G4.2 XXX			
	B.LINE PLUS L-G4.2 XXX			
	B.LINE PRO L-G4.1 XXX			
	B.LINE PRO L-G4.2 XXX			
Hyundai	HiS-MXXXTI	40 psf	30 psf	10.2 psf
	HiS-SXXXTI			
Jinko	JKMXXXP-60	N/A	30 psf	30 psf
	JKMXXXP-72			
LG	LGXXXN2W-G4	30 psf	18.8 psf	15 psf
	LGXXXN2W-A5			
	LGXXXN1C-A5			
	LGXXXN1K-A5			
	LGXXXS1C-A5			
	LGXXXS2W-A5			
ReneSola	JCXXXM-24/Ab	N/A	30 psf	15 psf
	JCXXXM-24/Bb			
REC	RECXXTP2 BLK2	50 psf	26 psf	15 psf
	RECXXTP2 BLK			
	RECXXTP2			
	RECXXTP			
	RECXXTP BLK			
	RECXXPE			
	RECXXPE BLK			
Talesun	TP672P-XXX	30 psf	20 psf	12 psf
	TP672M-XXX			
Trina	TSM-XXX PA05.08	N/A	30 psf	30 psf
S-Energy	SNXXXP-15	30 psf	20 psf	10 psf
	SNXXXP-10			
	SNXXXM-10			
	SNXXXM-10 (40T)			
	SNXXXP-10 (40T)			



Manufacturer	Module Series	Max. Downforce w/Mid-span Supports	Max. Downforce w/o Mid-span Supports	Max. Uplift
Silfab	SLG-M XXX SLG-P XXX SLG-X XXX SSG-M XXX SSG-P XXX	30 psf	13.9 psf	13.1 psf
	SLA-M XXX SLA-P XXX SLA-X XXX SSA-P XXX SSA-M XXX	40 psf	30 psf	13.3 psf
SolarWorld	SW Poly Pro SW Poly 2.5 Sunmodule Plus SW Mono Sunmodule Protect SW Mono	N/A	30 psf	30 psf
Yingli	YLXXXP-29b YLXXXC-30b	N/A	30 psf	30 psf

Notes:

- Testing is underway for module data listed as N/A and will be available soon.
- Testing for loads on downslope are not required for ballasted racking.
- The above list is not exhaustive. New modules are being tested on an ongoing basis. Contact Ecolibrium Solar directly for specific module information and Letters of Completion from TÜV Rheinland.



Release Notes		
Revision	Reason	Effective Date
1.0	Initial Release	4/25/17
1.1	<p>Modules Added:</p> <p>Boviet Solar BVM6612 P-XXX BVM6612 P-XXX (BB) BVM6612-M-XXX BVM6612 M-XXX (BB) BVM6610P-XXX BVM6610M-XXX BVM6610M(BB)-XXX BVM6610P(BB)-XXX</p> <p>Hyundai HiS-M3XXTI HiS-S3XXTI</p> <p>Canadian Solar CS6U-XXXXP CS6U-XXXXM CS6U-XXXXP (1500V) CS6U-XXXXM (1500V)</p> <p>ReneSola JCXXXM-24/Bb</p> <p>Silfab SLG-M XXX SLA-P XXX SLA-X XXX SLG-P XXX SLG-X XXX SSA-P XXX SSA-M XXX SSG-M XXX SSG-P XXX</p> <p>Modules Updated: Jinko JKMXXXM-72 LG LGXXXN2W-G4 ReneSola JCXXXM-24/Ab</p>	5/17/17
1.2	<p>Modules Added</p> <p>Canadian Solar CS6P-XXXXM</p> <p>ET Solar ET-M672XXXWW</p>	9/18/17



Release Notes		
Revision	Reason	Effective Date
1.2 (con't.)	ET-M672XXXWB ET-P672XXXWW ET-P672XXXWB ET-M672XXXBB ET-P672XXXBB Hanwha Q Cells Q.PRO BFR-G4.1 XXX Q.PEAK-G4.1 XXX Silfab SLA-M XXX SSA-M XXX SolarWorld SW Poly Pro SW Poly 2.5 Sunmodule Plus SW Mono Sunmodule Protect SW Mono Talesun TP672P-XXX TP672M-XXX Yingli YLXXXC-30b Modules Updated: Silfab SLG-M XXX SLG-P XXX SLG-X XXX SSG-M XXX SSG-P XXX SLA-P XXX SLA-X XXX SSA-P XXX Hanwha Q Cells Q.PRO BFR-G4 XXX Q.PLUS BFR-G4.1 XXX Q.PRO BFR-G4.3 XXX Q.PEAK BFR-G4.1 XXX (removed) Q.PEAK-G4.1/MAX XXX Q.PEAK BLK G4.1 XXX Q.PRO G4 XXX Q.PLUS G4 XXX Q.PEAK-G4.1/TAA XXX	



Release Notes		
Revision	Reason	Effective Date
1.2 (con't.)	Q.PEAK BLK G4.1/TAA XXX Q.PLUS BFR G4.1/TAA XXX Q.PLUS BFR G4.1/MAX XXX B.LINE PLUS BFR G4.1 XXX B.LINE PRO BFR G4.1 XXX Q.PRO EC-G4.4 XXX Q.PLUS L-G4.2 XXX Q.PEAK L-G4.2 XXX Q.PLUS L-G4.1 XXX Q.PLUS L-G4 XXX Q.PRO L-G4 XXX Q.PRO L-G4.1 XXX Q.PRO L-G4.2 XXX B.LINE PLUS L-G4.2 XXX B.LINE PRO L-G4.1 XXX B.LINE PRO L-G4.2 XXX Jinko JKMXXM-72 changed to JKMXXP-72	
1.3	Modules Added: S-Energy SNXXP-15 SNXXP-10 SNXXM-10 SNXXM-10 (40T) SNXXP-10 (40T) LG LGXXN2W-A5 LGXXN1C-A5 LGXXN1K-A5 LGXXS1C-A5 LGXXS2W-A5 REC RECXXTP2 BLK2 RECXXTP2 BLK RECXXTP2 RECXXTP RECXXTP BLK RECXXPE RECXXPE BLK	12/06/2017



Release Notes		
Revision	Reason	Effective Date
1.3 (con't.)	Modules Revised: Canadian Solar CS6X-XXXP (50 psf downforce w/mid-span supports added) LG LGXXXN2W-G4 (Max. downforce w/out mid-span support changed to 35 psf)	

Ecolibrium Solar® is a registered trademark of Ecolibrium Solar, Inc. EcoFoot2+™ is a trademark of Ecolibrium Solar, Inc. Copyright © 2017 by Ecolibrium Solar, Inc. All rights reserved.